

DISINFECTANT TUNNEL - ASSEMBLING TYPE (4pcs)

**HIGH-LEVEL
DISINFECTANT
& SANITISER**



Product	Arch Type Disinfectant Tunnel (Assembling Type)			
No. of assemblies	4 Assemblies	<ul style="list-style-type: none"> • Side panels : 2 pcs • Top panel : 1 pc • Base panel : 1 pc 		
Materials of Construction	Acrylic Sheet Aluminium Tube (powder coated)			
Product color	RAL 5015 (9005 for base) from Jotun			
Flooring	Galvanized Sheet			
Size	Width	Height	Length	Arch Dia
	1050 mm	2340 mm	2010 mm	1040 mm
Operational Function	<ul style="list-style-type: none"> <input type="checkbox"/> Mist activated by a float switch which in contact with the floating floor hanged on tension springs. <input type="checkbox"/> When pedestrian enter to tunnel, by weight, float switch get activated followed by energization of mist pump. <input type="checkbox"/> System will be back to sleep once the pedestrian out from the tunnel. 			
Disinfectant Tank Capacity	1,000 Litre min per unit			
Pump	Special Diaphragm pump, DC 12 V with AC adaptor (or) DC 24 V with AC adaptor			
Electrical power requirements	Single Phase 230 / 220 V AC			
Disinfectant solution	SHIELDme HOCL solution (to be bought separately)			

**HIGH-LEVEL
DISINFECTANT
& SANITISER**



DISINFECTANT TUNNEL - ASSEMBLING TYPE (4pcs)

